

A close-up photograph of a person's hand holding a roll of TYPAR Clear Acrylic Flashing tape. The person is wearing a dark shirt, tan pants, and a brown leather tool belt. The tape is white with the TYPAR logo printed on it. The background is a plain, light-colored wall.

# CLEAR ACRYLIC FLASHING



**THE VISIBILITY YOU WANT. WITH THE SEALING POWER YOU NEED.**

Install the system. Get a lifetime limited warranty.  
TYPAR® Clear Acrylic Flashing, along with the full TYPAR®  
Weather Protection System delivers unbeatable coverage.\*

\*Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at [TYPAR.com/downloads](http://TYPAR.com/downloads) for full details.





# TYPAR® CLEAR ACRYLIC FLASHING

## SEEING IS BEING SURE.

Smart. Strong. And nothing else like it around. TYPAR Clear Acrylic Flashing improves visibility of the nail or screw pattern on the window nailing fin so you can be confident that each window is installed correctly. Forget feeling around with hands or trying to lift up what's already stuck on. This saves time for installers, helps inspectors, and importantly, can head off costly callbacks. TYPAR Clear Acrylic Flashing is clearly a high-performer, too, designed with premium, advanced acrylic adhesive that is waterproof, self-sealing, and able to be applied even under cold conditions.

## LEADING FEATURES AND BENEFITS:

- Self-sealing around nails, screws, and fasteners for a waterproof seal
- UV-resistant up to 9 months
- Advanced acrylic adhesive that can be applied as low as 20° F (-6.7° C)
- Clear film allows visibility of nail/screw fin pattern
- Meets AAMA 711-22 industry standard for flashing tapes
- Split release liner for easy film removal
- Lifetime limited warranty coverage\*

## INSTALL THE SYSTEM. GET A LIFETIME LIMITED WARRANTY.\*

Looking for comprehensive defense? TYPAR Clear Acrylic Flashing is part of the industry's most complete weather protection lineup that includes wraps, flashings, tapes, sealant, and more. All manufactured by us for true ruggedness and higher performance.

### TYPICAL CHARACTERISTICS:

Adhesive	Clear acrylic
Backing	Clear film
Release Liner	Split-back clear film
Thickness w/Release Liner	12 mils
Application Temperature Range	20°F (-6.7°C) to 180°F (82°C)
Ultraviolet Light Exposure Resistance	9 months
Low Temperature Flexibility (ASTM D3330)	PASS
Nail Sealability (ASTM D1970)	PASS
Tensile Strength (ASTM D5034)	30 lbs

### ROLL SIZES (WITH LINER):

4" x 75'	6" x 75'	9" x 75'	12" x 75'
----------	----------	----------	-----------

\*TYPAR Clear Acrylic Flashing is part of the TYPAR® Lifetime Limited System Warranty when used with the complete TYPAR® Weather Protection System. Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at [TYPAR.com/downloads](https://www.typar.com/downloads) for full details.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **we make no warranties, express or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located online at [TYPAR.com/downloads](https://www.typar.com/downloads), subject to the limitations and exclusions described therein.**



September 2024 | Made in USA of US and Global Components.  
Please visit [TYPAR.com](https://www.typar.com) for installation instructions and warranty information.  
Building Wraps | Flashings | Construction Tape

