



DRAINABLEWRAP™ PEEL AND STICK

DEFEND AGAINST EXCESS MOISTURE WITHOUT EXCESS EFFORT.

Install the system. Get a lifetime limited warranty.* TYPAR® DrainableWrap Peel and Stick, along with the full TYPAR® Weather Protection System, delivers unbeatable coverage.

*Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.





TYPAR® DRAINABLEWRAP™ PEEL AND STICK

READY TO BEAT BULK WATER AND TIGHT TIMELINES?

Rely on our one-of-a-kind technology that gives enhanced drainability to our already superior weather barrier material. TYPAR DrainableWrap Peel and Stick is available in 4' 10" rolls so you can cover more area than the average peel-and-stick quickly—without having to worry about which direction you're applying it. With the name TYPAR® comes market-leading trust in defending structures from the elements. And with the ability to peel, stick, and keep moving, comes an edge in staying on schedule.

LEADING FEATURES AND BENEFITS:

- Delivers ease and speed of peel-and-stick installation
- Provides the tear strength, air holdout, drainability, and breathability of TYPAR® DrainableWrap™
- Drains significantly faster than conventional house wraps, per ASTM E2273 testing, with 94.8% efficiency
- Reduces penetrations from fasteners to help create a tighter building envelope
- Installs in any direction without affecting performance
- Offers improved cold temperature performance versus competition; installs down to 10°F (-12°C) without need of primer

INSTALL THE SYSTEM. GET A LIFETIME LIMITED WARRANTY.*

Our DrainableWrap Peel and Stick, along with our Flashings and Construction Tape, works as a part of the TYPAR® Weather Protection System. Install it all together and get the only lifetime limited warranty in the industry.

TYPICAL CHARACTERISTICS:

Basis Weight	D5261	4.2 oz/yd²
Thickness	D1777	22.9 mils
Drainage Efficiency	E2273	94.8%
Peel Adhesion to Substrates: - OSB - Vinyl - Anodized - Plywood Aluminum	D3330	>2 lbs/in
Cold Temperature Pliability	C765	PASS
Breaking Strength (Grab Tensile)	D5034	67 lbs MD 73 lbs CD
Trapezoidal Tear Strength	D5433	30 lbs MD 33 lbs CD
Hydrostatic Pressure Resistance	AATCC 127-1995	>500 cm
Moisture Vapor Transmission Rate	E96-95	10 perms
Ultraviolet Light Exposure Resistance		6 months
Air Permeance	E2178	<.01 l/m² @ 75 Pa
Air Penetration Resistance (Gurley Hill Porosity)		>2500 sec/ 100cc
Water Resistance Test	D779	PASS
Surface Burning Characteristics (ASTM E84)		
Flame Spread Index		Class A
Smoke Spread Index		PASS
ROLL SIZE:		
4' 10" x 100'		

*TYPAR DrainableWrap Peel and Stick is part of the TYPAR Lifetime Limited System Warranty when used with the complete TYPAR Weather Protection System. Certain limitations and exclusions apply. See the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads for full details.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **we make no warranties, express or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located online at TYPAR.com/downloads, subject to the limitations and exclusions described therein.**

NOTE: TYPAR DrainableWrap Peel and Stick is not available in Canada. ICC-ES #1404.



January 2025 | Made in USA. TYPAR® and TYPAR® DrainableWrap™ Peel and Stick are trademarks of Magnera Corporation or one of its affiliates. Please visit TYPAR.com for installation instructions and warranty information.
Building Wraps | Flashings | Construction Tape | Sealant

